PREMIER 8 RETAINING WALL











This revolutionary block design makes Premier the most efficient SRW blocks ever. Weighing nearly half that of comparable SRW's, they beat all other block systems for freight efficiencies and ease of construction.

- Easy-to-handle for increased efficiencies in the field
- Straight-thru core design; cores fill quickly & easily
- Ability to construct tight radius turns
- Cap with 4" Universal or Chiseled Cap
- Available by pallet



The 4 x 2" anchor bar on the underside of Premier 8 creates an automatic 1" (7°) setback with the highest shear resistance in the industry.



Blocks	Dimensions	Face Area	Weight	Units/Layer	Layers	Units/Pallet	Pallet Weight
Premier 8	18 x 12 x 8" H	1 sq. ft.	57 lbs.	9	5	45 (45 sq. ft.)**	2,615 lbs.
Solid Corner*	18 x 9 x 8" H	1 sq. ft.	100 lbs.	5	4	20 (20 sq. ft.)	2,050 lbs.

Corners are split on one long and one short side. *Rochester and Beaver Dam only. Dimensions shown are nominal. ** 36 units/pallet from Rochester, 2,102 lb. pallet. Manufactured in accordance with ASTM C1372.



7200 Broadway Ave. N, Rochester, MN 55906 Phone: 507-288-8850 • Fax: 507-535-1487

www.rochestercp.com





