

Block Dimensions

Classic 6

General Information

Absorption...meets or exceeds ASTM c90-75 standards
 Compressive strength...3000 PSI approximate minimum (unless otherwise specified)
 Composition . . . hight strength, high density, "0" slump concrete

Unit Information


Beveled Classic Unit:
 18" Beveled Split Face 6"H X 18" W, 56 Lbs. Approx. 0.75 Sq. Ft. Face

Straight Classic Unit:
 18" Straight Split Face 6"H X 18"W, 58 Lbs. Approx. 0.75 Sq. Ft. Face


Universal Cap Straight Split Face 4"H X 18"W front and 4"H X 14"W back, 54 Lbs. approx.
 0.50 Sq. Ft. Front, 0.39 Sq. Ft. Back
 Average running length is 16" (see installation manual)

Face Options


Face patterns Beveled Split Face
 Straight Split Face
 Rustic Face




Classic Universal Cap - Front



Beveled Classic 6" Unit



Classic Universal Cap - Back



Straight Classic 6" Unit


This drawing is furnished for preliminary design purposes only, and should not be used for final design drawings or construction drawings without the certification of a professional engineer registered in the state in which the wall will be constructed

No.	Date.	Revision.	By.

PREPARED BY:



LEGEND

	Impermeable Compacted Fill		3/4" Crushed Stone
	Compacted Fill		Leveling Pad
	Native Soil		Geogrid

Project Name: XX
 Project Location: YY
 Drawing Description: Block Dimensions

Prepared for: CCC
 DDD
 Drawn by: Checked by:
 Sheet # of \$
 Date: MM/DD/YYYY
 Project Number: WWWPRO#